

Superior Bungee Corporation

Mil-C-5651D Load Specifications

Age Dating Color Codes			
YEAR	MARKER	QUARTER	MARKER
2000	2blk	1st	1red
2001	2grn	2nd	1blu
2002	2red	3rd	1grn
2003	2blu	4th	1yel

CERTIFIABLE: CERTIFIABLE TO SPEC

NON CERTIFIABLE: NOT CERTIFIABLE TO SPEC
MANUFACTURER CERTIFICATION AVAILABLE



TYPE III SPECIFICATIONS



TYPE I DOUBLE COVER

DIAMETER	STRETCH	LOW	HIGH	
PART#:125C21MIL297				NON CERTIFIABLE
1/8" (.125-.172)	50%	2.5 lbs	3.5 lbs	
	75%	3 lbs	5 lbs	
	100%	5 lbs	8 lbs	

MIN BREAK 40 lbs
MIN STRETCH 140%

PART#:187C21MIL295				NON CERTIFIABLE
3/16" (.187-.234)	50%	5 lbs	8 lbs	
	75%	6 lbs	10 lbs	
	100%	9 lbs	14 lbs	

MIN BREAK 80 lbs
MIN STRETCH 140%

PART#:250C21MIL524 CERTIFIABLE

1/4" (.250-.297)	50%	8 lbs	12 lbs
	75%	10 lbs	18 lbs
	100%	16 lbs	28 lbs

MIN BREAK 120 lbs
MIN STRETCH 140%

PART#:312C21MIL205 NON CERTIFIABLE

5/16" (.312-.359)	50%	12 lbs	19 lbs
	75%	16 lbs	28 lbs
	100%	25 lbs	44 lbs

MIN BREAK 160 lbs
MIN STRETCH 140%

PART#:375C21MIL147 CERTIFIABLE

3/8" (.375-.422)	50%	30 lbs	60 lbs
	75%	50 lbs	100 lbs
	100%	90 lbs	150 lbs

MIN BREAK 300 lbs
MIN STRETCH 140%

PART#:500C21MIL158 CERTIFIABLE

1/2" (.500-.540)	50%	80 lbs	120 lbs
	75%	110 lbs	190 lbs
	100%	175 lbs	250 lbs

MIN BREAK 400 lbs
MIN STRETCH 140%

PART#:625C21MIL156 CERTIFIABLE

5/8" (.625-.672)	50%	100 lbs	180 lbs
	75%	160 lbs	250 lbs
	100%	250 lbs	350 lbs

MIN BREAK 500 lbs
MIN STRETCH 140%

PART#:750C21MIL293 CERTIFIABLE

3/4" (.750-.797)

50%	200 lbs	350 lbs
75%	300 lbs	450 lbs
100%	400 lbs	650 lbs

MIN BREAK 1000 lbs
 MIN STRETCH 120%



[back to top](#)



TYPE III SINGLE COVER

Age Dating Color Codes

YEAR	MARKER	QUARTER	MARKER
2000	3blk	1st	1red
2001	3grn	2nd	1blu
2002	3red	3rd	1grn
2003	3blu	4th	1yel

DIAMETER	STRETCH	LOW	HIGH
PART#:125C11MIL216			
1/8" (.125-.156)	50%	1 lbs	2.5 lbs
	75%	1.9 lbs	3.4 lbs
	100%	2.4 lbs	4.5 lbs
	125%	2.9 lbs	5.4 lbs
MIN BREAK	30 lbs		
MIN STRETCH	200%		

CERTIFIABLE

PART#:187C11MIL233			
3/16" (.187-.218)	50%	2 lbs	6 lbs
	75%	4 lbs	8 lbs
	100%	6 lbs	10 lbs
	125%	8 lbs	12 lbs
MIN BREAK	45 lbs		
MIN STRETCH	200%		

CERTIFIABLE

PART#:250C11MIL204			
1/4" (.250-.281)	50%	3 lbs	8 lbs
	75%	6 lbs	10 lbs
	100%	7 lbs	12.5 lbs
	125%	9 lbs	15 lbs
MIN BREAK	60 lbs		

NON CERTIFIABLE

MIN STRETCH 200%

PART#: 312C11MIL232 CERTIFIABLE

5/16" (.312-.343)	50%	5 lbs	10 lbs
	75%	6 lbs	12 lbs
	100%	8 lbs	15 lbs
	125%	10 lbs	18 lbs

MIN BREAK 75 lbs
MIN STRETCH 200%

PART#: 375C11MIL208 NON CERTIFIABLE

3/8" (.375-.406)	50%	9 lbs	15 lbs
	75%	13 lbs	19 lbs
	100%	17 lbs	23 lbs
	125%	21 lbs	27 lbs

MIN BREAK 140 lbs
MIN STRETCH 200%



[back to top](#)

Copyright ©1999 Superior Bungee Corporation. All rights reserved.

Reproduction in whole or in part in any form or medium without express written permission of Superior Bungee Corporation is prohibited. Please contact us at (256) 259-3770 or write us: Superior Bungee Corporation, 429 West Laurel Street, Scottsboro, Alabama, 35768